

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/062519 A2

(51) International Patent Classification⁷: **H04L 7/00**
(21) International Application Number:
PCT/IB2004/052726
(22) International Filing Date: 9 December 2004 (09.12.2004)
(25) Filing Language: English
(26) Publication Language: English
(30) Priority Data:
03104849.9 19 December 2003 (19.12.2003) EP
(71) Applicant (for all designated States except US): **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventors; and
(75) Inventors/Applicants (for US only): **SPINDLER, Robert** [AT/AT]; Triester Strasse 64, A-1101 Vienna (AT). **SCHERABON, Christian** [AT/AT]; Triester Strasse 64, A-1101 Vienna (AT). **BRANDL, Roland** [AT/AT]; Triester Strasse 64, A-1101 Vienna (AT).


(74) Agents: **RÖGGLA, Harald** et al.; Philips Intellectual Property & Standards, Triester Strasse 64, A-1101 Vienna (AT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: SYNCHRONIZATION DURING ANTI-COLLISION



(57) Abstract: An RFID system comprises at least one reading device (1) and at least one transponder (2, 2', 2'', 2'''), which are configured for non-contact communication by means of modulated electromagnetic signals (SS), which contain data and/ or commands packed in data frames, in which the reading device (1) is configured for transmitting a group of data frames (D-SYNC), which contain synchronization information (Preamble, Start Delimiter) for synchronization with the transponder (2, 2', 2'', 2''') and to transmit another group of data frames (D-NOSYNC) which do not contain such synchronization information, in which the transponder (2, 2', 2'', 2''') has synchronization means (14, 20, 21) which are configured to effect synchronization with the reading device (1) with the help of synchronization information (Preamble, Start Delimiter) contained in received data frames (D-SYNC) and synchronization status test means (15, 15', 15'', 22) configured for detecting whether the transponder runs synchronously with the reading device and in the event of it not running synchronously, to switch on the synchronization unit (14, 20, 21).



Published:

— without international search report and to be republished
upon receipt of that report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.